

FPF 2 SERIES

Non-Metallic Fixture for Food Processing


- NSF Certified Food Equipment
- High Pressure Hose Down
- UL 924 Emergency Lighting
- UL 1598A Wet Locations
- Non-Metallic Fluorescent Fixture
- CUL



AZZ | R-A-L™
RIG-A-LITE

FPF 2 SERIES

Non-Metallic Fixture for Food Processing



- Indoor or outdoor use
- High pressure hose down
- Emergency option available

FLUORESCENT

FPF 2 Series

Non-Metallic Housing • UL 1598 Wet Locations • CUL • High Pressure Hose Down • Indoor or Outdoor • NSF Certified

Catalog Number Logic

FPF2 265-8-2L-U-XX

1

2

3

4

5

6

1

BASIC SERIES¹

FPF2 Non Metallic Fluorescent Fixture
UL 1598 Wet Locations
CUL
NSF Certified Food Equipment

5

VOLTAGE/FREQUENCY

A = 120V 60HZ
C = 277V 60HZ
H = 347V 60HZ¹
U = 120 thru 277V 50/60 HZ

2

LAMP WATTAGE

380 = 380mA, 86 Watt
265 = 265mA, 59 or 32 Watt (T8 Lamps)
T5HO = T5HO 54 Watt (n/a in 2 foot)

6

OPTIONS²

AL95 = Premium Specular Reflector
F = Individually Fused Ballast
FM = Stainless Steel Fixed Mount
HL = Hi-Lumen Ballast (T8 Only)
L = Lamps
LC = Coated Lamps
R = Radio Interference Filter
SS = Stainless Steel End Caps
1UP = Uplight (2 down & 1 up)
EON = Emergency Only
ENN = Emergency & Normal
ENS = Emergency & Normal Switched

3

NOMINAL FIXTURE LENGTH

2 = 2 Foot
4 = 4 Foot
8 = 8 Foot

4

NUMBER OF LAMPS

1L = 1 Lamp
2L = 2 Lamp
3L = 3 Lamp
4L = 4 Lamp (8 ft. T5HO Only)
6L = 6 Lamp (8 ft. T5HO Only)
Not Available as Emergency
Uplight Options Available Consult Factory

¹ Fixtures are furnished with FPFXDMKT, non-metallic cord grip and 3 ft. long #16 AWG 3 conductor type SOA cable.

² Consult factory for pricing.

Catalog logic is for explaining catalog number structure only. Not all combinations are possible; consult factory for catalog numbers not listed in charts.

FLUORESCENT FPF 2 Series

Non-Metallic Housing • UL 1598 Wet Locations • CUL • High Pressure Hose Down • Indoor or Outdoor • NSF Certified

Fluorescent Series



- UL 1598 Wet Locations
- CUL
- Unique design tolerates high temperatures and high pressure hose down
- No flat surfaces to collect contaminants
- Non metallic, thermoplastic housing eliminates the need to utilize special shatter proof lamps
- Stainless steel external hardware and mounting
- All models come standard with electronic energy saving ballast
- Standard 3 ft. leads or water-tight disconnects available
- Specular reflector standard - premium reflector available
- NSF Certified Food Equipment
- Optional stainless steel end caps available

Fluorescent Emergency Series



- Emergency illumination meets OSHA, Life Safety Code (NFPA 101), and National Electric Code (NFPA 70) requirements
- Switched or non-switched applications
- Provides 1100-1200 lumens of initial light output in emergency mode
- Provides at least 90 minutes of illumination in emergency mode
- Sealed, maintenance-free nickel cadmium batteries with a life expectancy of 7-10 years
- Self Contained unitized construction
- Easily identified as an emergency lighting fixture
- Charging indicator LED pilot light
- Battery cut-off switch is standard
- NSF Certified Food Equipment

FLUORESCENT

FPF 2 Series

Non-Metallic Housing • UL 1598 Wet Locations • CUL • High Pressure Hose Down • Indoor or Outdoor • NSF Certified


Fluorescent Series

(Lamps not included)

	Description	Voltage	Catalog Number*
Four Foot Fixture	32 Watt, Rapid Start Medium Bi-Pin, 265mA 2 Lamps, 48"	120-277V 50/60HZ	FPF2265-4-2L-U
	54 Watt, T5HO miniature Bi-Pin 3 lamps, 48"	120-277V 50/60HZ	FPF2T5HO-4-3L-U
Eight Foot Fixture	32 Watt, Rapid Start Medium Bi-Pin, 265mA 4 Lamps, 48"	120-277V 50/60HZ	FPF2265-8-4L-U
	54 Watt T5HO miniature Bi-Pin 6 Lamps, 48"	120-277V 50/60HZ	FPF2T5HO-8-6L-U
	59 Watt, Rapid Start Slimline, T-8 Single Pin 265mA, 2 Lamps, 96"	120-277V 50/60HZ	FPF2265-8-2L-U
	86 Watt, High Output, T-8 Recessed Double Contact 380mA, 2 Lamps, 96"	120-277V 50/60HZ	FPF2380-8-2L-U

Fixtures are furnished with stainless steel chain mount kit, non-metallic cord grip and 3 ft. long #16 AWG 3 conductor type SOA cable.

Fixture Dimensions (inches)



FPF 2 SERIES	Dimensions (Inches)		Boxed Weight	Shipping Volume (Boxed Fixtures)
	A	B		
2 Foot Models	28.00	6.75	10 lbs.	1.2 cu. ft.
4 Foot Models	52.00	6.75	20 lbs.	2.1 cu. ft.
8 Foot Models	100.00	6.75	30 lbs.	4.0 cu. ft.

FLUORESCENT

FPF 2 Series

Non-Metallic Housing • UL 1598 Wet Locations • CUL • High Pressure Hose Down • Indoor or Outdoor • NSF Certified

Fluorescent Emergency Series

Fixture Type	Circuit Type	Nominal Fixture Length	Description	Voltage	Catalog Number
Emergency Only Operation	Non-Switched ¹	Two Foot 2 Lamp Fixture	17 Watt, Instant Start, Medium Bi-Pin, T8 265mA Lamps, 24"	120-277V 50/60HZ	FPF2265-2-2L-U-EON
		Four Foot 2 Lamp Fixture	32 Watt, Instant Start, Medium Bi-Pin, T8 265mA Lamps, 48"	120-277V 50/60HZ	FPF2265-4-2L-U-EON
Emergency and Normal Operation	Non-Switched ¹	Four Foot 2 Lamp Fixture	32 Watt, Instant Start, Medium Bi-Pin, T8 265mA Lamps, 48"	120-277V 50/60HZ	FPF2265-4-2L-U-ENN
			54 Watt, T5HO Miniature Bi-Pin Lamps, 48"	120-277V 50/60HZ	FPF2T5HO-4-2L-U-ENN
		Four Foot 3 Lamp Fixture	54 Watt, T5HO Miniature Bi-Pin Lamps, 48"	120-277V 50/60HZ	FPF2T5HO-4-3L-U-ENN
		Eight Foot 2 Lamp Fixture	59 Watt, Rapid Start, Slimline Single Pin, T8 265mA Lamps, 96"	120-277V 50/60HZ	FPF2265-8-2L-U-ENN
		Eight Foot 4 Lamp Fixture	32 Watt, Instant Start, Medium Bi-Pin, T8 265mA Lamps, 48"	120-277V 50/60HZ	FPF2265-8-4L-U-ENN
			54 Watt, T5HO Miniature Bi-Pin Lamps, 48"	120-277V 50/60HZ	FPF2T5HO-8-4L-U-ENN
	Switched ²	Four Foot 2 Lamp Fixture	32 Watt, Instant Start, Medium Bi-Pin, T8 265mA Lamps, 48"	120-277V 50/60HZ	FPF2265-4-2L-U-ENS
			54 Watt, T5HO Miniature Bi-Pin Lamps, 48"	120-277V 50/60HZ	FPF2T5HO-4-2L-U-ENS
		Four Foot 3 Lamp Fixture	54 Watt, T5HO Miniature Bi-Pin Lamps, 48"	120-277V 50/60HZ	FPF2T5HO-4-3L-U-ENS
		Eight Foot 2 Lamp Fixture	59 Watt, Rapid Start, Slimline Single Pin, T8 265mA Lamps, 96"	120-277V 50/60HZ	FPF2265-8-2L-U-ENS
		Eight Foot 4 Lamp Fixture	32 Watt, Instant Start, Medium Bi-Pin, T8 265mA Lamps, 48"	120-277V 50/60HZ	FPF2265-8-4L-U-ENS


¹Non-Switched fixtures are furnished with stainless steel chain mount kit, non-metallic cord grip and 3 ft. long #16 AWG 3 conductor type SOA cable.

²Switched fixtures are furnished with stainless steel chain mount kit, non-metallic cord grip and 3 ft. long # 16 AWG 4 conductor type SOA cable.

FLUORESCENT FPF 2 Series

Non-Metallic Housing • UL 1598 Wet Locations • CUL • High Pressure Hose Down • Indoor or Outdoor • NSF Certified

Accessories



Fixed Mounting Bracket Kit

Stainless Steel - For 3/8 in. Bolts (Not Provided)

Catalog Number: FPFXDMKT

Shipping Weight: 0.4 lbs.




Chain Mounting Kit

Stainless Steel

Catalog Number: FPFCMKT1

Shipping Weight: 0.2 lbs.




Mini Plug 3P - 6 ft. Mini Cable

Other Lengths Available - Consult Factory

Catalog Number: 60006


Shipping Weight: 0.6 lbs



Mini Receptacle 3P Male

Catalog Number: 64005

Shipping Weight: 0.1 lbs




Pigtail Assembly- 3 ft. Cable

Other Lengths Available - Consult Factory

Catalog Number: 53108

Shipping Weight: 0.5 lbs.



Stainless Steel Band Clamp

Catalog Number: FPFBNMKT


Shipping Weight: 1.0 lbs.

FLUORESCENT FPF 2 Series

Non-Metallic Housing • UL 1598 Wet Locations • CUL • High Pressure Hose Down • Indoor or Outdoor • NSF Certified

Parts List

CATALOG NUMBER FPF2380-8-2L-U



- Note: 1. Above drawing and part numbers are for fixture catalog no. FPF2380-8-2L-U.
 2. Parts may vary for other models. Contact factory if parts for other models are required.
 3. Ballasts and lamps are listed on separate pages.

FLUORESCENT

FPF 2 Series

Non-Metallic Housing • UL 1598 Wet Locations • CUL • High Pressure Hose Down • Indoor or Outdoor • NSF Certified

Parts List

Part No.	Description	Weight
02092	BLST FLUOR 380MA 8FT 120-277V 50/60 HZ	5.0
Y00068	LAMP FLUOR 380MA HO RDC	5.5
23067	REFLECTOR FPF800-8	5.5
23079	REFLECTOR FPF2 SPECULAR REFLECTOR	1.0
26507	CLOSURE PLATE NON ELECT END	0.2
26508	CLOSURE PLATE ELECT END	0.1
26509	COVER BLST FPF-8	0.7
28005	SCREW HEXWSHRSLT	0.1
28010	EYE BOLT	0.1
28027	SCREW HEXWSHRSLT	0.1
28040	SCREW HEXWSHRSLT	0.1
28081	SCREW PAN	0.1
28186	NUT HEX	0.1
28222	WASHER THREADED	0.1
28234	WASHER FLAT	0.1
28246	WASHER SPLIT LOCK	0.1
28248	WASHER SPLIT LOCK	0.1
28325	NUT HEX	0.1
28335	SCREW RDH CARRIAGE	0.1
28337	NUT HEX TINMAN	0.1
34100	GSKT MOUNTING BRKT	0.1
34101	GSKT MALE DISCONNECT	0.1
34102	GSKT END CAP FPF	0.1
59014	END CAP ELEC FPF	0.5
59015	END CAP NON ELEC FPF	0.5
59016	TUBE CLEAR	7.5
70011	LPHLDR FLUOR REC DOUB TELE	0.1
70048	LPHLDR FLUOR REC DOUB FXD	0.2
82062	WIRE U/L-CSA GRN 16AWG	0.1
84073	LUG RNG N/INS 16-14AWG	0.1
59014SS	END CAP ELEC FPF SS	0.5
59015SS	END CAP NON ELEC FPF SS	0.5
34102F	END CAP GASKET FPFSS	0.1

NOTES